

Azure® ECM

Condenser Fan Applications

Ball Bearing

Azure® is an electronically controlled motor (ECM) that replaces a multitude of applications. These motors cover ratings from 1/8 HP to 1/3 HP at 208-230V 825/1075 RPM and 1/3 HP to 1/2 HP 208-230V 825/1075 RPM and CW or CCW. These motors are simple to install. The Azure® condenser fan motors connect the same as a standard PSC condenser fan motor, BUT WITHOUT the capacitor. Just plug the motor into a 115V power source (using supplied programming cable) and select 1 of 4 operating modes and then install the motor:


- 1) 1075 RPM CW (LE) -
Factory Default
- 2) 1075 RPM CCW (LE)
- 3) 825 RPM CW (LE)
- 4) 825 RPM CCW (LE)

Unlike other ECM motors, an outboard surge protector is included with the Azure® wiring harness. This is a replaceable device that is much less expensive to replace than replacing the entire motor in the event of a power surge.

Specifications:

- Multi horsepower, self-adjusting
- 825/1075 RPM, single speed
- Reversible rotation
- High efficiency ECM
- No capacitor required
- Water slinger on shaft
- UL Recognized
- For accessories see page M-5

| MARS NO. | HP | VOLTS | RPM | ROTATION | ORIENTATION | RHEEM HOLES | DIMENSIONS | | |
|----------|-----------|---------|----------|----------|-------------|-------------|------------|------|-----|
| | | | | | | | A | B | C |
| 10874 | 1/8 - 1/3 | 208-230 | 825/1075 | Rev | Shaft Down | Yes | 6.50 | 4.33 | 1/2 |
| 10875 | 1/8 - 1/3 | 208-230 | 1075 | Rev | Horizontal | No | 6.50 | 4.33 | 1/2 |



Azure® ECM


3.3" Commercial Refrigeration Evaporator Fan Motor

Ball Bearing

Azure® is an electronically controlled 3.3" motor (ECM) that replaces all 1/15 - 1/25 HP, 115/230V, and 1550/600 RPM commercial refrigeration evaporator fan motors for walk in cooler/freezer applications. For 1550 RPM, this motor connects easily to the fan controller via a standard Lyall plug. For 2-speed applications, the Lyall plug can be removed and the motor can be wired directly to a separate 2-speed control module using the included second speed tap for 600 RPM. Motor rotation is set using a simple jumper wire. Azure® is rated for 115V or 230V with nothing to set; plug it in to either voltage and it adapts to the correct voltage.

Specifications:

- Operating temperature range: -40° to 131°F
- Multi horsepower, self adjusting from 1/15 to 1/25HP
- Reversible rotation
- Auto voltage select (115/230V)
- High efficiency ECM technology
- No capacitor required
- UL Recognized
- For accessories see page M-5



| MARS NO. | HP | VOLTS | RPM | SPEEDS | ROTATION | DIMENSIONS | | |
|----------|-------------|---------|---------------------|-----------------------|----------------------|------------|------|------|
| | | | | | | A | B | C |
| 10850 | 1/15 - 1/25 | 115/230 | 1550 | 1 | Rev | 2.5 | 3.74 | 5/16 |
| 10852 | 1/15 - 1/25 | 115/230 | 1550 ⁽¹⁾ | 1 or 2 ⁽²⁾ | CCWLE ⁽³⁾ | 2.5 | 3.74 | 5/16 |

(1) 1550 default; adjustable 600-2000 RPM with optional wireless programmer kit (MARS No. 08505)

(2) 2-speeds attainable with optional wireless programmer (MARS No. 08505) and optional thermistor kit (MARS No. 08515)

(3) CCWLE default; reversible with optional wireless programmer (MARS No. 08505)